

BATTERY ANALYZER



1.This machine is for 12V vehicle battery only. 2.Do not store the machine in high temp or humidity place, so as to prevent the machine from damage.

Rating: Not Rated Yet

Price:

Sales price:

Discount:

[Ask a question about this product](#)

Manufacturer: [HCB Specialty Tools](#)

Description

Product Description :
BATTERY ANALYZER

?Product Info?

Model/Item No. :

H.C.B-A2142

Country of Origin :

Taiwan

Brand :

H.C.B

Product Specifications /Features :

***Notice**

- 1.This machine is for 12V vehicle battery only.
- 2.Do not store the machine in high temp or humidity place, so as to prevent the machine from damage.
- 3.The working voltage range is 9V~15V DC, do'nt operate on series battery(24V).
- 4.Operate after turning on the headlight 3-5 minutes to clean the surface voltage when the battery is full recharged.

***JIS Battery Model Convert Chart**

- 1.Please refer th the CCA values marked on the battery.
- 2.This tavle shows reference value of common JIS battery specification.
- 3.See the manual for details.
- 4.For testing single 12V battery only.
- 5.CMF: Closed Maintenance Free, MF: Maintenance Free

Primary Competitive Advantages :

GENERAL REPAIR EQUIPMENTS : BATTERY ANALYZER

Well and High Quality Control, Prompt Delivery, Customer's Design and Logo are Welcome, Competitive Prices

Sales Method :

Export, Manufacture

Payment Term :

T/T, L/C at Sight



Battery Model		Cold Cranking Amp (CCA)		
JIS(New)	JIS(Old)		MF	CMF
28A19	12N24-4	200	220	264
32C24	N40	240	325	400
34B19	NS40ZA	270	325	400
36B20	NS40Z	275	300	360
38B20	NX60-N24	330	340	410
48B24	N960	325	360	420
48D26	N50	280	360	420
50D20		310	360	480
55D23		355	480	500
55B24	NX100-86	435	420	500
55D26	N90Z	350	440	525
65D23		420	540	590
65D26	NS70	415	520	625
70D23	35-60	490	540	560
75D23		500	520	580
75D31	N70Z	450	540	735

80D26	NX110-S	580	580	630
95E41	N100	515	640	770
105E41	N100Z	580	720	880
115E41	NS120	650	800	900
115F51	N120	650	800	900
145G51	N150	780	900	1100
190H52	N200	925	1100	1300