

## STRAIGHT EDGE



\*Great stability with 5/8" width, 1-3/8" height and 20-1/2" length. Convenient hanging hole and edge protector.

Rating: Not Rated Yet

**Price:**

Sales price:

Discount:

[Ask a question about this product](#)

Manufacturer: [HCB Specialty Tools](#)

Description

**Product Description :**

**STRAIGHT EDGE**

**?Product Info?**

**Model/Item No. :**

**H.C.B-A2033**

**Country of Origin :**

**Taiwan**

**Brand :**

**H.C.B**

**Product Specifications /Features :**

\* GREAT STABILITY WITH 5/8" WIDTH, 1-3/8" HEIGHT AND 20-1/2" LENGTH.

\* CONVENIENT HANGING HOLE AND EDGE PROTECTOR.

\* USE FEELER GAUGES TO CHECK FOR DISTORTION IN ENGINE BLOCKS, CYLINDER HEAD AND FLYWHEELS.

\* G.W:2.4 KGS

\* MATERIAL: S50C

\* HARDNESS: HRC43?-48?

\* PARALLEL ACCURACY: ±3?

\* L x W x H: 600x16x36mm

\* CHECK FOR WARPAGE ACROSS THE HEAD SURFACE WITH THE HEADCLEAN AND DRY.

\* USE A PRECISION STRAIGHT-EDGE AND A FEELER GAUGE TO MEASURE THE HEAD FOR WARPAGE.

\* IF IT IS LESS THAN 0.002" (0.05 mm), RESURFACING IS NOT REQUIRED. IF WARPAGE IS BETWEEN 0.002-0.008" (0.05-0.2 mm), THE HEAD MUST BE RESURFACED. THE STANDARD IS 95 mm (3.66"). THE MAX SURFACING CLEARANCE IS 0.008" (0.2 mm).

**Primary Competitive Advantages :**

Well and High Quality Control, Prompt Delivery, Customer's Design and Logo are Welcome, Competitive Prices

**Sales Method :**

Export, Manufacture

**Payment Term :**

T/T, L/C at Sight

